

IN THE CLAIMS

1. (currently amended): A ~~recharging device of batteries~~ battery recharging device for batteries (6), ~~which can also be used as an exhibitor~~ and for the display of battery packs or packagings (5) ~~in sales points at a point of sale, said battery charging device~~ comprising at least a supporting element (1, 17, 51), which includes a series of seats or housings (2, 18) for the insertion and/or linking of packs of batteries battery packs (5) on at a point of sale, and means (20, 30) for the charging, recharging and/or maintenance of the electric charge, electrically connected to said seats or housings (2, 18) of the recharging device wherein each pack of batteries (5) of batteries (6) contains batteries, connected in series to each other, of which at least two terminals (7, 8, 80) are accessible from the outside of the pack of batteries (5) for connection to the recharging and/or maintenance means (20, 30) of an electric charger
2. (currently amended): The battery recharging device ~~[[6]]~~ according to claim 1, characterized in that it also comprises at least one suitable housing (4) for checking the charge level of battery packs (5), which can said suitable housing (4) being adapted to be used for the temporary resting support of one of said battery packs (5), whose charge level is to be checked.
3. (canceled)
4. (currently amended): The battery recharging device ~~[[6]]~~ according to claim 1, characterized in that said electronic recharging and maintenance means of the electric charger, by automatically recognizing, thanks to a control logic (50), the housing of at least one pack of batteries (5), immediately activates a charging cycle of said housing of the battery pack (5) inside at least one of said housings seats (2, 18).
5. (currently amended): The battery recharging device ~~[[6]]~~ according to claim 1, characterized in that each of said housings ~~or seats~~ (2, 18) comprises signaling means, suitable for indicating the charge level and/or the arrival at the maximum charge level of the battery pack (5) that is inserted.

6. (currently amended): The battery recharging device [[[6)]] according to claim [[3]] 1, characterized in that said two terminals (7, 8, 80) are situated at different distances (~~D1, D2, D3~~), in order to be able to automatically select the necessary charge levels for the various types of batteries (6) to be charged.

7. (currently amended): The battery recharging device [[[6)]] according to claim [[3]] 1, characterized in that said at least one supporting element (1, 17, 51) comprises, in correspondence with each seat or housing (2, 18), at least one metallic body (27), pushed by at least a first elastic conductor element (28), ~~of the elastic type~~, which ensures ~~the~~ electric contact with said at least two terminals (7, 8, 80) of the battery pack (5), whereas at least a second conductor element (29) produces the electric contact with said recharging ~~and/or maintenance~~ means of the electric charger.

8. (currently amended): The battery recharging device [[[6)]] according to claim [[3]] 1, characterized in that at least one of said terminals (7, 8, 80) contacts at least one spring nail (38), in turn electrically connected to said recharging ~~and/or maintenance~~ means (20, 30) of the electric charger.

9. (currently amended): The battery recharging device [[[6)]] according to claim 8, characterized in that said ~~battery packaging or~~ pack (5) is held in position thanks to a notched ~~profile~~ (42) of said at least one supporting element (1, 17, 51), which is engaged with an incision situated on the packaging (5).

10. (currently amended): The battery recharging device [[[6)]] according to claim [[3]] 1, characterized in that said ~~battery packaging or~~ pack (5) has at least one guiding wing (46) for insertion inside said ~~seats and/or~~ housings (2, 18) and is also equipped with at least one inductor element (44) and/or at least one rectifier diode (45), said at least one supporting element (1, 17, 51) comprising at least one magnetic circuit (47), with polar expansions, on which at least one ~~coiling~~ (48) is wound, so that, upon insertion of the ~~packaging~~ battery pack (5) in the respective ~~seat and/or~~ housing (2, 18), said inductor element (44), inserted between said polar expansions of the magnetic circuit (47), forms an inductive magnetic coupling with said coiling (48), so as to

transfer the electric energy, supplied by an alternating current generator (49) and rectified by said diode (45), to the batteries (6) of the battery pack packaging (5).

11. (currently amended): The battery recharging device [[[6)]] according to claim 1, characterized in that said at least one supporting element (1, 17, 51) comprises automatic selection and supply means of at least one of said battery packs (5), driven by an electronic panel control logic (50), when a selection is effected by a user by means (10, 11, 12, 32, 33, 34) situated on the outer casing (35) of the recharging device.

12. (currently amended): The battery recharging device [[[6)]] according to claim 11, characterized in that said at least one supporting element (1, 17, 51) includes a series of columns (13, 14, 16, 20, 26, 37), inside which the battery ~~packagings or packs~~ (5) ~~are arranged, which~~ are introduced into appropriate ~~seats~~ slits (18) and kept in a horizontal position by means of shelves (15).

13. (currently amended): The battery recharging device [[[6)]] according to claim 11, characterized in that ~~said control and running logic~~ electronic panel (50) selects at least one battery pack (5) containing the most highly charged batteries (6) of the type selected.

14. (currently amended): The battery recharging device [[[6)]] according to claim 11, characterized in that said automatic selection and supply means comprise at least one pin (91) of an expeller, kept in rest position by at least a first elastic element (92), and at least one ~~coiling~~, which, after the passage of an electric current, generates an entrainment force ~~[[of]]~~ on said pin (91) of the compression of said first elastic element (92), which produces the expulsion of the ~~packaging battery pack~~ (5) and the falling of said ~~packaging battery pack~~ (5) onto a collection surface (36).

15. (currently amended): The battery recharging device [[[6)]] according to claim 14, characterized in that said at least one supporting element (1, 17, 51) is electrically connected, by means of at least a second elastic element (96), with a body (94), associated with at least a third elastic element (95) and suitable for contacting at least one terminal (80) of the battery pack (5)

for the charging of the batteries (6) contained therein.

16. (currently amended): The battery recharging device [[(6)]] according to claim 1, characterized in that said battery ~~packaging or~~ pack (5) is made up of two symmetrical shells (23, 24) which mechanically withhold the batteries (6) and leave the relative terminals free, so that each battery (6) can be charged individually.

17. (currently amended): The battery recharging device [[(6)]] according to claim 11, characterized in that said battery ~~packagings or~~ packs (5) are stacked on top of each other, in correspondence with each column (13, 14, 20, 16, 26, 37).

18. (currently amended): The battery recharging device [[(6)]] according to claim 11, characterized in that said automatic selection and supply means comprise at least one motor (28), whose rotation produces the moving of at least one pushing element (27) which causes the release of each battery ~~packaging or~~ pack (5) from the withholding elastic elements (29, 43).

19. (currently amended): The battery recharging device [[(6)]] according to claim 11, characterized in that said automatic selection and expulsion means comprise at least one pushing element (27B), moved by at least one belt (26B), in turn activated by at least one motor (28B).